



GIBUS

Med Varia

Bioclimatic Aluminium Pergola.



Maximum single unit dimensions : 7.2m by 4.5m



Honesty
Full price transparency online.




Design Team
Helping you create your dream



Install network
Options nationwide with flexible coverage



Peace Of Mind
Available across all products



The Med Varia is the new Gibus bioclimatic flat roof pergola system. The fully integrated side closures hidden within the unique design allows the coupling of sliding glass and vertical shade screens for exceptional all year round protection. Available in wall mounted or freestanding island configurations.

In Summary

The louvre blades are able to rotate to any position within a range of 0-135° allowing for your preferred lighting and to release or capture heat. The aluminium 13x13cm square upright posts have a 25cm perimeter with a frame height of 240cm. Integrated downpipes channel rain water off the blades, into the gutters and out the posts.



Average Cost Per Square Meter (inc VAT)

	Width →			
Projection ↓	< 3m	< 4m	< 5m	5m >
< 3m	£2,200	£1,700	£1,500	£1,350
< 4m	£1,750	£1,400	£1,200	£1,100
< 5m	£1,550	£1,250	£1,100	£1,000
< 6m	£1,400	£1,100	£1,000	£900
< 7m	£1,350	£1,100	£950	£900
7m >	£1,350	£1,050	£950	£850


Example
 Width = 5.5m
 Projection = 4.5m
 → 24.75m² coverage
 → ~ £1000 per m²
 Estimate cost of
 £24,750 inc VAT

Med Joy : Bioclimatic Pergola

Roof System: Louvred

Page 2 of 2

Key Features



Rain Protection

The blades in the closed position effectively protect against rain, dispatching rainwater into the drainage channels



Sun Protection

The aluminium cover gives optimal protection of direct sun radiation, allowing full control of the amount of light that filters inside



Ventilation

A pleasant and cooling breeze is enjoyed by slightly opening the blades to create the natural flow of air that rises.

Popular Options



Integrated Shade Screens

Vertical integrated down blind equipped with guides including ZIP system with spring for complete wind and rain protection



Glisse Sliding Glass Walls

Sliding glass walls on stainless steel tracks, in 2, 3 or 4 way solutions and up to 8 doors without perimeter profiles. Toughened safety glass from 10 to 12mm thick



Skate Folding Glass Walls

Sliding and folding wall panels made of toughened 10mm safety glass without perimeter profiles.



RGB LED Strips

RGB LED strips applied along the inside perimeter. Set a single colour choice from 7 options: white, yellow, orange, red, green, blue and purple. Or create your own light program.



Perimeter LED Spots

Rectangular LED spotlights integrated inside the perimeter gutter of the structure. Arranged every 50 cm in groups of 6 per light point, each 3 Watts.



Blade LED Spots

Rectangular 3 watt LED spotlights integrated inside the blades to guarantee excellent light distribution over the entire surface covered.